




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : E21B 33/12	A1	(11) International Publication Number: WO 99/45233 (43) International Publication Date: 10 September 1999 (10.09.99)
(21) International Application Number: PCT/SE99/00328 (22) International Filing Date: 4 March 1999 (04.03.99) (30) Priority Data: 9800684-4 4 March 1998 (04.03.98) SE (71)(72) Applicant and Inventor: ALEXANDERSSON, Hans [SE/SE]; Kaprifolvägen 5, S-513 00 Fristad (SE). (74) Agent: AWAPATENT AB; P.O. Box 11394, S-404 28 Göteborg (SE).		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>In English translation (filed in Swedish).</i>

(54) Title: SEALING FOR ENERGY WELLS**(57) Abstract**

The present invention relates to a method and a device in wells, and preferably energy wells, for sealing thereof, said wells being of a kind comprising a well casing (1) and circulation pipes (2) extending inside said well casing, preferably for the circulation of a heat-exchange medium. According to the invention a tubular gasket (4) is fitted around the circulation pipes (2) so as to enclose the latter at least around part of their extension lengthwise and is arranged at the lower part of said well casing (1), a material (6) of a kind that expands upon its contact with a liquid, and in consequence thereof becomes sealing, being applied about the tubular gasket (4) to seal between said tubular gasket and the well casing (1).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

SEALING FOR ENERGY WELLS

The present invention relates to a method and a device in wells, and preferably energy wells, for sealing thereof, said wells being of a kind comprising a well casing and circulation pipes extending inside said well casing, preferably for the circulation of a heat-exchange medium.

In for example energy wells or water wells it is often of considerable importance that water and contaminants present in the upper earth strata that contain soil and sand do not flow down into the bore-hole drilled in the rock. To prevent this from happening it is common practice to drive a well casing down through the earth stratum and the upper rock strata, which are often fissured and therefore a potential risk that surface water and polluting matter present therein penetrate into the bore-hole. Alternatively, the well casing could be driven down in conjunction with the very hole-drilling operation, in which case an end cap, known as the drill shoe, of metal or other heavy material is attached to the end of the well casing.

Into the well casing and the drilled hole, two pipes are inserted so as to extend in parallel, through which pipes flows the medium by means of which heat exchange is carried out relative to the rock and the water supplies contained therein. At their top, the pipes lead to a heat pump or the like.

It is, however, also desirable that sealing is provided in the interior of the well between the upper part passing through the upper earth strata and the lower part extending into the rock, in order to efficiently prevent surface water and the like, often acidified, from reaching the groundwater.

Also, it is desirable to be able to make better use of the energy well and to extract more energy therefrom.

Consequently, one object of the invention is to provide means for more efficient sealing of wells, and in particularly of energy wells.

This object is achieved by means of a device and a
5 method as defined in the appended claims.

For exemplifying purposes the invention will be described in more detail in the following with reference to the accompanying drawing figure, which shows the lower part of an energy well fitted with a seal in accordance
10 with the invention.

An energy well designed in accordance with one embodiment of the invention, shown in the drawing figure, comprises a well casing 1 inside which circulation pipes 2 are located. Inside these circulation pipes a medium
15 circulates, for example for a heat pump (not shown). The well casing is driven down through the soft surface layers of earth and sand and further down, into the rock. Preferably, the well casing comprises a stiff lower-end portion 3, acting as a drill shoe, which could be
20 attached to the well casing by means of e.g. welding. Obviously other methods of fastening the shoe are likewise possible.

Furthermore, a tubular gasket 4 is arranged around at least some of the circulation pipes. For sealing
25 between the circulation pipes and the tubular gasket a sealing compound 5 is placed between the pipes and the seal, said sealing compound preferably being of the type that swells upon its contact with a liquid. Consequently, the tubular gasket may easily be fitted over the cir-
30 culation pipes while at the same time efficient sealing is achieved upon contact with a liquid, i.e. when sealing is required. The tubular gasket is disposed inside the well casing, and for this purpose it is configured with an external diameter that is at least slightly smaller
35 than the inner diameter of the well casing. Also between the tubular gasket 4 and the well casing 1 there is positioned a sealing compound 6, the latter likewise

preferably being of a liquid-expandable kind. Preferably, the sealing compound is located between concentric and essentially adjoining surfaces.

5 The sealing compounds 5, 6 preferably are applied in the form of strings inside keyways or similar grooves formed in the tubular gasket.

At its lower part intended to project beyond the lower part 3 of the well casing, the tubular gasket preferably comprises a third annulus 7 of a sealing compound, preferably of the same nature as those mentioned
10 previously, for the purpose of making sealing contact with the rock.

The lower part of the well casing preferably further comprises an inner upwardly facing abutment edge 8, i.e.
15 at the lower well casing part at least one section is formed with a smaller interior diameter than the rest of the casing. Furthermore, the tubular gasket 4 is formed with a matching downwards directed abutment edge 9. This abutment edge 9 of the tubular gasket preferably is
20 formed by configuring the upper part of the tubular gasket with a larger diameter than the lower part thereof. The larger diameter is only slightly smaller than the inner diameter of the well casing whereas the smaller diameter of the lower tubular gasket part is
25 smaller than the inner diameter of the abutment edge 8. Furthermore, the abutment edges 8, 9 preferably are inclined such that they slope downwards, towards the centre of the tubular gasket. This arrangement centres the tubular gasket as the latter is being passed down
30 into the casing while at the same time some additional sealing effect is achieved.

These abutment edges form abutment and stop means when the tubular gasket, after having been fitted around the circulation pipes, is pushed down through the well
35 casing. Additional sealing compound may optionally be applied in the area of the abutment means in order to seal between the tubular gasket 4 and the well casing 1.

Preferably, the sealing compounds are made from a material that swells upon its contact with a liquid. As an example of a material of this kind may be mentioned that marketed by the Japanese enterprise C.I. Kasei Co., Ltd under the trade name Hydrotite®. Preferably the string of material is introduced in the shape of an annulus into peripherally extending keyways of matching configuration provided for the purpose.

As long as the sealing member remains out of contact with liquid and consequently does not expand, the sealing pressure against the surfaces surrounding the sealing member is low. It is therefore easy to locate the various parts forming part of the sealing system in their correct relative positions. When exposed to liquid, the sealing compound will expand heavily and in consequence thereof be pressed into efficient sealing contact with the adjacent surfaces, thus efficiently preventing undesirable liquid and any contaminants contained therein from passing past the sealed-off parts and down into the well hole, which would result in pollution of the groundwater or at least of water present in the bore hole.

The sealing compound could also be of a kind exhibiting delayed swelling ability following its contact with a liquid. Such delayed response may be achieved by application of a gradually dissolving delay-layer on top of the sealing compound. Alternatively, the material as such may have a composition ensuring the delay activity. This delay feature facilitates the mounting work.

At its upwardly facing part, the tubular gasket further advantageously is formed with pull-up means to facilitate withdrawal of the tubular gasket. Such pull-up means may comprise e.g. a loop or the like, which may be coupled to a wire to allow the tubular gasket to be pulled up, out of the well casing. This allows retrieval of the tubular gasket, etcetera.

Preferably, the tubular gasket is made from a recyclable material, such as e.g. polyethylene (PE).

When an energy well having a well casing 1 has been placed inside the drill hole, the tubular gasket 4 is lowered down to the level of the drill shoe 3, where it is stopped and sticks as a result of its expansion. Owing to the efficient sealing effect obtained by means of the invention the level of water inside the drill hole may be increased by supply of water from above. This allows the well to be filled to a level located above the level of the groundwater, and possibly all the way up to ground level. In this manner, the quantity of water available for the heat exchange process becomes larger, allowing an increase of the amount of transferred energy. At the same time, the resulting well is guaranteed to be sealed off against surface water, which often may be acidified or contain other contaminants.

The circulation pipes could be part of a heat-pump system using a special heat carrier medium, as well as being water-carrying pipes used for supplying water from the associated well. The well could be used both for extraction of heat to a heat-pump system and for drawing drinking water. Also a combination of these kinds of pipes is possible without departure from the inventive idea. Likewise, it is possible to arrange the sealing compound differently from what has been shown herein and in other positions on the tubular gasket.

CLAIMS

1. A device in wells, and preferably energy wells,
for sealing thereof, said wells being of a kind
5 comprising a well casing (1) and circulation pipes (2)
extending inside said well casing, preferably for the
circulation of a heat-exchange medium, c h a r a c -
t e r i s e d by a tubular gasket (4), which is fitted
around the circulation pipes (2) so as to enclose the
10 latter at least around part of their extension lengthwise
and which is arranged at the lower part of said well
casing (1), a material (6) of a kind that expands upon
its contact with a liquid, and in consequence thereof
provides sealing, being applied about the tubular gasket
15 (4) to seal between said tubular gasket and the well
casing (1).

2. A device as claimed in claim 1, c h a r a c -
t e r i s e d in that a liquid-expandable material (6)
is applied also between the circulation pipes (2) and the
20 tubular gasket (4).

3. A device as claimed in claim 1 or 2, c h a r -
a c t e r i s e d in that at its lower, preferably rigid
end portion (3) said well casing (1) comprises an inner
upwardly facing abutment edge (8), and in that said
25 tubular gasket (4) comprises a matching downwards facing
abutment edge (9).

4. A device as claimed in any one of the preceding
claims, c h a r a c t e r i s e d in that in a section
of said tubular gasket (4) that projects downwards below
30 the well casing (1), said tubular gasket (4) also
comprises an external sealing annulus (7), preferably
made from a liquid-expandable material, for sealing
against the surrounding rock.


5. A device as claimed in claim in any one of the
35 preceding claims, c h a r a c t e r i s e d in that
the tubular gasket (4) may be pulled upwards via the well
casing (1).

6. A method for sealing wells, preferably energy wells, of a kind comprising a well casing (1) and circulation pipes (2) extending inside said well casing, c h a r a c t e r i s e d in that a tubular gasket (4) is applied around the circulation pipes (2) prior to the latter being lowered into the well casing (1), and in that a sealing compound (6) of a kind that expands upon its contact with a liquid is applied about the tubular gasket (4) for sealing between the tubular gasket and the well casing (1).

7. A method as claimed in claim 6, c h a r a c - t e r i s e d by applying a sealing compound (5), preferably of liquid-expandable type, between the tubular gasket (4) and the circulation pipes (2).

8. A method as claimed in claim 6 or 7, c h a r - a c t e r i s e d by arresting the tubular gasket (4), when lowering it into the well casing (1), in a lower position by means of an abutment (8), said abutment acting against an abutment (9) of matching configuration formed on the tubular gasket (4).

9. A method as claimed in any one of claims 6-8, c h a r a c t e r i s e d by applying an external sealing annulus (7), preferably of a liquid-expandable material, about the lower part of the tubular gasket (4) for sealing against the rock below the well casing (1).



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/00328

A. CLASSIFICATION OF SUBJECT MATTER		
IPC6: E21B 33/12 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by classification symbols)		
IPC6: E21B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
SE,DK,FI,NO classes as above		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
EPODOC, WPI		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	SE 469394 B (H. ALEXANDERSSON ET AL), 28 June 1993 (28.06.93), page 3, line 24 - page 5, line 16, figures 2,3 --	1-9
A	US 5195583 A (D.A. TOON ET AL), 23 March 1993 (23.03.93) --	1-9
A	US 5048605 A (D.A. TOON ET AL), 17 Sept 1991 (17.09.91) --	1-9
A	SE 466869 B (H. ALEXANDERSSON ET AL), 13 April 1992 (13.04.92) -- -----	1-9
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search		Date of mailing of the international search report
19 May 1999		20 -06- 1999
Name and mailing address of the ISA Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86		Authorized officer Christer Bäcknert Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

Information on patent family members

03/05/99

International application No.

PCT/SE 99/00328

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
SE	469394	B	28/06/93	AT 152210 T	15/05/97
				BR 9206665 A	24/10/95
				DE 69216847 D,T	16/10/97
				DE 69310159 D	00/00/00
				EP 0609346 A,B	10/08/94
				EP 0629259 A,B	21/12/94
				JP 7502209 T	09/03/95
				RU 2087300 C	20/08/97
				SE 9200730 A	28/06/93
				US 5488215 A	30/01/96
				WO 9318274 A	16/09/93
US	5195583	A	23/03/93	CA 2052308 A	28/03/92
				GB 2248255 A,B	01/04/92
US	5048605	A	17/09/91	AT 73895 T	15/04/92
				AU 612332 B	11/07/91
				AU 8175887 A	01/06/88
				CA 1291947 A	12/11/91
				DE 3777663 A	23/04/92
				EP 0331676 A,B	13/09/89
				GB 2197363 A,B	18/05/88
				IN 169647 A	30/11/91
				JP 2501582 T	31/05/90
				WO 8803597 A	19/05/88
SE	466869	B	13/04/92	DE 69025625 D,T	01/08/96
				EP 0505426 A,B	30/09/92
				SE 9000817 A	09/09/91